

FLUKE SPECIFICATIONS AND PRICES

{ [HYPERLINK](#) }

MonarchDirect Item No.	7803-1201	7803-1202	7803-1203	7803-1210	7803-1211	7803-1212	7803-1213
Model	Fluke 63	Fluke 66	Fluke 68	Fluke 572	Fluke 574	Fluke 574-NI	Fluke 576 Photo
PRICE (USD)	\$215.00	\$405.00	\$519.00	\$753.00	\$1,161.00	\$2,327.00	\$1,797.00
Temperature range	-32 to 535 °C (-25 to 999 °F)	-32 to 600 °C (-25 to 1100 °F)	-32 to 760 °C (-20 to 1400 °F)	-30 to 900 °C (-25 to 1600 °F)	-30 to 900 °C (-25 to 1600 °F)	-30 to 900 °C (-25 to 1600 °F)	-30 to 900 °C (-25 to 1600 °F)
D:S (Distance to spot size) at 90% energy	12:1	30:1	50:1	60:1 (50:1 with close focus option)	60:1 (50:1 with close focus option)	60:1 (no close focus option).	60:1 (50:1 with close focus option)
Laser sighting	Single point, offset			extra bright 3-dot, coaxial			
Emissivity	Preset 0.95	Adjustable		Adjustable	Adjustable	Adjustable	Adjustable
Accuracy (Assumes ambient operating temperature of 23 °C [73 °F])	± 1 % of reading or ± 1 °C (± 2 °F), (whichever is greater over the balance of the range)			± 0.75 % of reading or ± 0.75 °C (± 1.5 °F) (whichever is greater over the balance of the range)			
Response time	500 mSec			250 mSec	250 mSec	250 mSec	250 mSec
Display Hold	N/A			7 sec	7 sec	7 sec	7 sec
MAX, MIN, DIF and AVG	MAX only	All		Min. and Max only	Yes	Yes	Yes
Recall last reading	N/A	Yes		N/A	100-point data logging		
HI/LO alarm	N/A	Yes	Yes	HI=Yes LO=No	Yes	Yes	Yes
Bar graph display	N/A	N/A	N/A	Yes	Yes	Yes	Yes
Max Photos 640 x 480 pixels VGA	N/A	N/A	N/A	N/A	N/A	N/A	26 jpeg files
Max Photos 320 x 240 pixels VGA	N/A	N/A	N/A	N/A	N/A	N/A	100 jpeg files
Weight and dimensions (H x W x L)	320 g (11 oz) and 200 x 160 x 55 mm (8 x 6 x 2 in)			472 g (1 lb 1 oz.) and 16.7 x 5 x 19.8 cm (6.58 x 1.97 x 7.8 in)	480 g (1 lb 1 oz) and 16.7 x 5 x 19.8 cm (6.58 x 1.97 x 7.8 in)		580 g (1 lb 4 oz) and 23.8 x 5 x 16.7cm (9.57 x 1.97 x 6.58 in)
Power	9 V alkaline			2 AA Batteries	2 AA Batteries/AC adapter		2 AA Batteries/USB
Display hold	7 seconds			7 seconds	7 seconds	7 seconds	7 seconds
LCD backlit	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Warranty	2 years, conditional			2 years, conditional			
Software	N/A			N/A	Data graphing software (Windows XP, NT, 2000 compatible, RS232 port required)		Data graphing and image viewing software (Windows XP, NT, 2000 compatible, USB port required)
Kit Contents	Thermometer, 9V alkaline battery, operators guide, CD-ROM with user manual and a Latching Hard Case.			Thermometer, (2) AA batteries, user manual and latching hard case.	Thermometer, (2) AA batteries, AC power supply, thermocouple K, RS-232 cable, Windows compatible software, user manual and latching hard case.		Thermometer, (2) AA batteries, thermocouple K, USB cable, Windows compatible software, user manual and hard case.

FLUKE SPECIFICATIONS AND PRICES
 "www.monarchdirect.biz" }

{ [HYPERLINK](#) }

Fluke	MD	Description	Height	Length	Width	Weight	Country	US
Model #	Item Number		(Metric / English)				of origin	List Price
80PR-60	7803-1251	RTD Probe used on the Fluke 66/68	30.2 cm/11.8 in	9.8 cm/3.8 in	2.9 cm/1.1 in	0.0528 kg/0.1165 lb	China	\$54.00
H6	7803-1252	Holster used on the Fluke 63/66/68	30.2 cm/11.8 in	5.7 cm/2.25 in	17.8 cm/7 in	0.1494 kg/0.3295 lb	China	\$30.00
C570	7803-1253	Soft Case for 500 Series	25 cm/10 in	17.8 cm/7 in	6 cm/2.3 in	.163 kg/0.36 lb	Poland	\$45.00
AN5	7803-1254	Cable Analog Output for Model 574	2.5 cm/0.98 in	1.5 m/5 ft	14 cm/5.5 in	.055 kg/0.121 lb	Germany	\$54.00